



Technical data	
Shore hardness A	40 +/- 5
Tensile strength	>8MPa
Elongation at rupture	> 600%
Temperature resistance	-30 °C / 90 °C
Flame resistance	UL 94-VO/m3



Type	Cable Diameter mm	Length mm	Wall Thickness mm	Color	Tool
A3ZW	5.0-9.0	25	0.7	BLACK	KY3
A4ZW	7.5-12.0	30	0.8	BLACK	KY3
A5ZW	10.5-15.0	35	0.9	BLACK	KY3
A8ZW	12.0-20.0	50	1.2	BLACK	KY4
A9ZW	14.0-23.0	50	1.3	BLACK	KY4
A10ZW	17.0-28.0	50	1.3	BLACK	KY4

Type	Cable Diameter mm	Length mm	Wall Thickness mm	Color	Tool
A3GR/G	5.0-9.0	25	0.7	Yellow/ Green	KY3
A4GR/G	7.5-12.0	30	0.8	Yellow/ Green	KY3
A5GR/G	10.5-15.0	35	0.9	Yellow/ Green	KY3
A8GR/G	12.0-20.0	50	1.2	Yellow/ Green	KY4
A9GR/G	14.0-23.0	50	1.3	Yellow/ Green	KY4
A10GR/G	17.0-28.0	50	1.3	Yellow/ Green	KY4



Type	Range
KY3 Sleeve Expander	A2-A2K-A3-A4-A5
KY4 Sleeve Expander	A5-A8-A9-A10

Ultra-lightweight tools, with nylon/carbon-fibre composite handles and hardened steel prongs. They have an adjustable 'stop' which can be set to prevent over-expanding

BV Betonindustrie , Albert Einsteinweg 19 , 5151 DK Drunen ,T: 0416-370067,
E:info@bvbetonindustrie.nl.